

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US04/018413

International filing date: 09 June 2004 (09.06.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US
Number: 60/477,528
Filing date: 11 June 2003 (11.06.2003)


Date of receipt at the International Bureau: 19 August 2004 (19.08.2004)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse

1207504



THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office

August 09, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/477,528
FILING DATE: *June 11, 2003*
RELATED PCT APPLICATION NUMBER: *PCT/US04/18413*

Certified by

Jon W Dudas

Acting Under Secretary of Commerce
for Intellectual Property
and Acting Director of the U.S.
Patent and Trademark Office





17712 U.S. PTO

612-03

60477528 06/11/03

PTO/SB/16 (05-03)

Approved for use through 4/30/2003. OMB 0851-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No.

EV 094 354 132 US

14712 U.S. PTO

60/477528



06/11/03

Given Name (first and middle (if any))		Family Name or Surname		Residence (City and either State or Foreign Country)	
Charles		Perkins		Boston, Massachusetts	
Additional inventors are being named on the <u>1</u> separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
DETECTION OF LARGE LEAKS IN HERMETICALLY SEALED COMPONENTS WITH A SMALL INTERNAL VOLUME					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input checked="" type="checkbox"/> Customer Number		23693			
OR		Type Customer Number here			
<input type="checkbox"/> Firm or Individual Name		PATENT TRADEMARK OFFICE			
Address					
Address					
City		State		ZIP	
Country		Telephone		Fax	
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		3		<input type="checkbox"/> CD(s) Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		2		<input checked="" type="checkbox"/> Other (specify) Return Receipt Postcard	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees.					
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		50-0895		\$160	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are:					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME

Bella Fishman

TELEPHONE

650.424.5086

[Page 1 of 2]

Date

6/11/03

REGISTRATION NO.

37,485

(If appropriate)

Docket Number:

03-19 US PRO

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

63477523 .051103

PROVISIONAL APPLICATION COVER SHEET
Additional Page

PTO/SB/16 (05-03)
 Approved for use through 4/30/2003. OMB 0851-0032
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Docket Number 03-19 US PRO

INVENTOR(S)/APPLICANT(S)		
Given Name (first and middle [if any])	Family or Surname	Residence (City and either State or Foreign Country)
Pieter	Palenstyn	Plympton, Massachusetts

[Page 2 of 2]

Number 1 of 1

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Docket No.: 03-19 US PRO



VARIAN

**DETECTION OF LARGE LEAKS IN HERMETICALLY SEALED COMPONENTS
WITH A SMALL INTERNAL VOLUME**

DESCRIPTION OF THE INVENTION

The invention concerns a new method for helium leak testing of, but not limited to, large-leak testing hermetically sealed components. The key feature is a sensor composed of a permeable material that selectively permeates helium. This could be, but not limited to, a polymer or a quartz material in any shape or form (sphere, cylinder, capillary, etc.). For applications where quartz is used, the quartz is heated by a heater, such as resistive, radiant, or other appropriate heat transfer means, to allow selective permeation of helium through the helium sensor. It is known that the permeation rate of helium can be controlled by temperature to adjust the sensitivity of the sensor. This new helium sensor can be used in a leak test system under vacuum, at ambient pressure, or at a slight over pressure.

In a conventional helium leak detection method, where a large leak is present in a small part, the helium can be pumped away so fast during the rough pump cycle that no leak reading is possible and the leaking part is accepted. This problem has existed in the industry for a very long time. The following methods have been utilized for some application with limited results.

- Measure the difference in evacuation time between a leaky or non-leaky part. (Not enough resolution)
- A volumetric expansion method. (Not enough resolution)

Figure 1 shows the configuration of a solution consisting of a vacuum flange, a vacuum enclosure, a sensor, a sputter ion pump, and a controller that supplies power to the ion pump and reads back the pump current. Alternately, a conventional leak detector can be used with the sensor assembly in various applications, for example, an application where a fine leak test is required after the large leak test. Figure 2 shows a configuration with a conventional leak detector.

Docket No.: 03-19 US PRO

The internal volume of the part to be tested has been previously pressurized with helium or has been exposed to a high helium concentration in a bombing chamber before inserting it into the test chamber of the leak detector

In the new concept, two vacuum chambers are inter-connected by a valve (A), while a vacuum pump is connected to the lower chamber via a valve (B). The helium sensor is connected to the lower chamber. With valve A closed to isolate the two chambers from each other, the part to be tested is inserted into the upper chamber. At the beginning of the test, the helium concentration in the chamber is at ambient levels or alternately, a nitrogen flushing operation can reduce the helium concentration to enhance sensitivity capability for the large leak measurement described in this paper.

With valve A closed, valve B is opened to pump a vacuum in the lower chamber. Valve B is then closed so there is no pumping in either chamber. Valve A is opened between the two chambers and the gas from chamber A is permitted to flow into the lower chamber until pressure equilibrium is achieved. Helium leaking from the test part passes into the lower chamber and increases the helium concentration in the vacuum environment until a pressure equilibrium is reached. The resulting helium concentration in the vacuum can be now be measured by the sensor or leak detector. Only helium will pass through the permeable window and increase the vacuum pressure in the sensor ion pump or leak detector. The resulting increase of ion pump current is proportional to the increase in helium pressure and the leak rate. For the leak detector configuration, the leak rate can be read directly. The key feature of this invention is that the helium sensor has zero pumping speed in the test chamber. It does not remove the gas from the vacuum environment as with prior art devices. It detects the helium leak, but does not pump the helium away so large leak detection is made more accurately, more reliably, and with more sensitivity than previous methods used in the industry. If no large leak is detected the conventional leak detector cycle can be continued, which means further evacuation of the chambers (with valve A open) and finally connecting the vacuum environment to the conventional leak detector, for example a mass spectrometer leak detector, for fine leak measurement


Docket No.: 03-19 US PRO

SUMMARY OF THE INVENTION

1. A leak test device made of permeable material of any shape or form (sphere, cylinder, capillary, etc.)
2. A heater (resistive, radiant, or a similar technology) heats the quartz material to allow helium permeation, while selectively blocking most other gases water and dust. A heater is not required where a permeable polymer, for example is used.
3. When heated to a certain temperature, the quartz material permeates helium at a constant rate.
4. The temperature can be adjusted to control the permeation rate and therefore the sensitivity.
5. The sensor can be installed at the inlet of an ion pump, which is power by a high voltage, between 2000 and 9000 volts. The ion pump current is proportional to the vacuum pressure inside the sensor. Helium that permeates through the quartz window affects the vacuum pressure at a rate proportional to the leak rate. The ion pump current is therefore proportional to the leak rate. Alternately, the sensor can utilize a conventional leak detector to read the helium concentration instead of the ion pump current.
6. The sensor can operate either with vacuum at the inlet flange or with atmospheric pressure at the inlet flange or at a pressure slightly higher than atmospheric.
7. The sensor can operate in an atmosphere that contains various gases, particles such as dust, or in wet environments.
8. The sensor can be installed as shown in Figure 1 and 2 and can be used for accurate testing for large leaks for parts of various sizes and is particularly useful for small volume parts with a large leak.

Docket No.: 03-19 US PRO

FIGURE 1 Helium Sensor for a Large Leak Test With Ion Pump



Docket No.: 03-19 US PRO

FIGURE 2 Helium Sensor for a Large Leak Test With Conventional Leak Detector

